

FIREPLACE COMPARISON

U33 & U33 TALL

Enjoy our newest gas fireplace single sided, see-through, or tall.



SPECIFICATIONS	U33		U33T		U37		U44					
BTU Max. Input NG / LP	40,000 BTUs		40,000 BTUs		47,000 BTUs		63,000 BTUs					
P4 Efficiency	TBA		TBA		36.6% 46.6%†		37.6% 47.6%†					
Turn Down	Up to 33%		Up to 33%		Up to 33%		Up to 33%					
Valve Configuration	IPI		IPI		IPI		IPI					
Venting	5" x 8"		5" x 8"		5" x 8"		5" x 8"					
Flex Venting	TBA		TBA		N/A		N/A					
Average Weight (Including liner and media)	200 lbs		300 lbs		400 lbs		489 lbs					
Viewing Area	1,062½ in²		1,875 in²		1,112 in²		1,586 in²					
Glass Dimensions <i>Safety Screen replaces outer glass on screened units</i>	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH				
	34"	35⅜"	60"	35⅜"	30⅝"	35⅜"	36⅝"	42⅜"				
Unit Dimensions	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
	44"	41"	17" SS 19" DS	62"	41"	17" SS 19" DS	44½"	46¼"	24¼"	50½"	53½"	27½"

*See owner's manual for detailed fireplace specifications. † Based on in-house testing using 5/8" vent SS: Single Sided, DS: Double Sided