

Traditional Fireplace Comparison



U33/U33T

U37

U44

BTU Max. Input - NG / LP	40,000 BTUs			47,000 BTUs			63,000 BTUs		
P4 Efficiency	TBA			36.6%			37.6%		
Turn Down	Up to 33%			Up to 33%			Up to 33%		
Valve Configuration	IPI			IPI			IPI		
Venting	5" / 8"			8" / 11" or 5" / 8"			8" / 11" or 5" / 8"		
Log Set	11 Piece Log Set			9 Piece Log Set			10 Piece Log Set		
Double Sided Compatible	Yes			N/A			N/A		
Glass Dimensions	HEIGHT 34" U33 74" U33 Tall		WIDTH 31 ¹ / ₄ "	HEIGHT 30 ¹ / ₈ "		WIDTH 35 ³ / ₁₆ "	HEIGHT 36 ⁵ / ₁₆ "		WIDTH 42 ³ / ₁₆ "
Unit Dimensions	HEIGHT 41" U33 81" U33 Tall	WIDTH 43"	DEPTH 17"SS 19"DS	HEIGHT 44 ¹ / ₂ "	WIDTH 46 ¹ / ₈ "	DEPTH 24 ⁷ / ₈ "	HEIGHT 50 ¹ / ₂ "	WIDTH 53 ³ / ₈ "	DEPTH 28"

*See owner's manual for detailed fireplace specifications.